CORNIX

PRODUCT DATASHEET

CNX-DS-F65-006 · REV 1.0 · 06 OCTOBER 2026

FIBER CONNECTIVITY · SINGLE-MODE FIBER PIGTAIL (G.657.A1)

Single-Mode G.657.A1 Pigtail, SC/UPC, 0.9 mm, 1.5 m

BEND-INSENSITIVE · ITU-T G.657.A1 · SIMPLEX & 12-FIBER SETS

PART NO. **CX-FPT-OS2B-SC-1.5M**

Also marked on products / QR labels as: CX-FG-SM-SC-1.5M

PRODUCT ILLUSTRATION



< 0.2 dB	≥ 50 dB	1.5 m	SC/UPC
INSERTION LOSS	RETURN LOSS	LENGTH	CONNECTOR

OVERVIEW

Single-ended pigtails on bend-insensitive G.657.A1 fiber, developed for fusion-splice termination in FTTH distribution boxes, splice closures, ODFs and patch panels. Offered as simplex pigtails and 12-fiber color-coded sets.

- Bend-insensitive ITU-T G.657.A1 fiber
- Insertion loss ≤ 0.2 dB, 100% tested
- 3.0 mm LSZH simplex, 0.9 mm and 12-fiber set options
- Zirconia ceramic ferrules
- Ideal for FTTH boxes, ODFs and patch panels

APPLICATIONS

- FTTH distribution and termination boxes
- Splice closures and ODFs
- Loaded patch-panel termination

STANDARDS & COMPLIANCE

RoHS compliant

Technical Specifications

Single-Mode G.657.A1 Pigtail, SC/UPC, 0.9 mm, 1.5 m · CX-FPT-OS2B-SC-1.5M

GENERAL

Connector	**SC/UPC**
Length	**1.5 m**

CONSTRUCTION

Ferrule	**Zirconia ceramic**
Buffer	**0.9 mm tight buffer, LSZH**
Jacket color	**Yellow**

OPTICAL CHARACTERISTICS

Fiber type	**Single-mode, ITU-T G.657.A1 (bend-insensitive)**


OPTICAL PERFORMANCE

Insertion loss	**< 0.2 dB**
Return loss	**≥ 50 dB**

Performance, Quality & Ordering

CX-FPT-OS2B-SC-1.5M

OPTICAL PERFORMANCE



INDIVIDUAL TEST REPORT — EVERY ASSEMBLY

100% IL / RL TESTED

Test item	Requirement	Method	Recorded on
Insertion loss	< 0.2 dB	IEC 61300-3-4	A1, A2
Return loss	≥ 50 dB	IEC 61300-3-6	A1, A2
End-face geometry & cleanliness	Pass	Interferometer / microscope	Each connector

Measured insertion and return loss values are printed on each unit's label and test sheet.

ORDERING INFORMATION

CX	FPT	OS2B	SC	1.5M
CORNIX	Pigtail	Single-mode G.657.A	SC connector	Length 1.5 m

Part number	Description
CX-FPT-OS2B-SC-12F-1.5M	Single-Mode G.657.A1 12-Fiber Color-Coded Pigtail Set, SC/UPC, 1.5 m
CX-FPT-OS2B-SC-12F-01M	Single-Mode G.657.A1 12-Fiber Color-Coded Pigtail Set, SC/UPC, 1 m
CX-FPT-OS2B-LC-1M	Single-Mode G.657.A1 Pigtail, LC/UPC, 1 m
CX-FPT-OS2B-LC-1M-APC	Single-Mode G.657.A1 Pigtail, LC/APC, 1 m
CX-FPT-OS2B-SC-1.5M	**Single-Mode G.657.A1 Pigtail, SC/UPC, 0.9 mm, 1.5 m**
CX-FPT-OS2B-SC-1.5M-APC	Single-Mode G.657.A1 Pigtail, SC/APC, 1.5 m
CX-FPT-OS2B-SC-1M-APC	Single-Mode G.657.A1 Pigtail, SC/APC, 1 m

8 part numbers in this family — full list in the family datasheet.

Request a quote or technical support

Datasheets, test reports and samples available on request

rfq@cornixglobal.com
sales@cornixglobal.com
cornixglobal.com

CORNIX® continuously improves its products; specifications are subject to change without notice. Values are maximum / minimum unless stated otherwise. Illustrations are representative. © 2026 CORNIX LLC. All rights reserved.